

View Online at <https://aerobasegroup.com/nsn/4720-01-371-1328>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

1.090 inches

Minimum Inside Bending Radius:

3.750 inches

End Application:

Aircraft, grumman standard, ka-60-dcn

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting aluminum alloy 6061 all ends

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

3600.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire err-100

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

1.0625 inches 1st end

External Protection Type And Location (non-core):

Both ends chafe guard, heat shrinkable pololefin tubing

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant

Inside Surface Condition:

Convuluted

Measuring Method And Length:

114.000 inches working

Special Features:

Anodize per mil-a-8625

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0