## NSN 4720-01-371-1329

**Cross Sectional Shape:** 

Round

Thread Class: 2b 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-371-1329

| Thread Direction:   |
|---|
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.407 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.820 inches  |
| Minimum Inside Bending Radius:  |
| 5.750 inches  |
| End Connection Design:  |
| Straight 1st end  |
| End Fitting Component And Material:   |
| Complete fitting stainless steel all ends   |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Second End Relationship With First End:   |
| Identical   |
| Burst Test Pressure:  |
| 10500.0 pounds per square inch  |
| First End Swivel Action Capability:   |
| Not included  |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire err-100                            |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Thread Size:  |
| 0.750 inches 1st end  |
| External Protection Type And Location (non-core):                                     |
| chafe guard, tetrafluoroethylene  |
| Seat Angle:   |
| 12.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 6000.0 pounds per square inch   |
| Inside Surface Condition:   |
| Smooth  |

18.000 inches

**Measuring Method And Length:** 

## NSN 4720-01-371-1329

Nonmetallic Hose Assembly - Page 2 of 2



| Special | Features: |
|---------|-----------|
|---------|-----------|

External protection type and location- chafe guard, tetrafluoroethylene, inner conveying tube material-plastic, tetrafluoroethylene

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0