## NSN 4720-01-371-1331

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-371-1331

0
Cross Sectional Shape:
Round
Thread Class:
1a 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.310 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response
Outside Diameter:
0.610 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
2815-01-335-4579
Connection Style:
Inverted flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 2nd end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer rubber impregnated fabric
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.625 inches 2nd end
Seat Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
63.320 inches
Media For Which Designed:
Air and fuel/oil hydrocarbon and water single response

Unf 2nd end

**Thread Series Designator:** 

## NSN 4720-01-371-1331

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0