Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-371-4394

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.312 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response	
Outside Diameter:	
Between 0.597 inches and 0.635 inches	
Minimum Inside Bending Radius:	
1.250 inches	
End Application:	
3930-01-275-6420, fork lift truck	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
4000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided textile yarn and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric	
Maximum Operating Pressure:	
1000.0 pounds per square inch	
Thread Size:	
0.625 inches 1st end	
Seat Angle:	
45.0 degrees 1st end	
Hydrostatic Test Pressure:	
2000.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
10.500 inches	
Thread Series Designator:	
Unf 2nd end	

NSN 4720-01-371-4394

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0