NSN 4720-01-371-4399

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-371-4399 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 0.810 inches **Minimum Inside Bending Radius:** 3.500 inches **End Application:** 2320-01-354-3387 **Connection Style:** Swivel nut, gasket seal 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 2nd end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and outer layer woven polyester fiber cord **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.812 inches 2nd end Flow Angle: 45.0 degrees 2nd end **Outer Covering Environmental Protection:** Abrasion resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:**

61.000 inches **Thread Series Designator:** Un 2nd end

NSN 4720-01-371-4399

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0