Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-371-4400

Cross Sectional Shape:         Round         Thread Class:         2b 1st end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.875 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         1.390 inches         Minimum Inside Bending Radius:         9.700 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         End Fitting Component And Material:         Complete fitting stainless steel all ends         Connection Type:         Thready Uy Per Inch (tpi):         12 1st end         Burst Test Pressure:         12000.0 pounds per square inch         First End Swivel Action Capability:         Not included         Layer Composition And Location:         With Ivard Size end         Maximum Operating Pressure:         1.312 inches 1st end         Straight 1st end         First End Swivel Action Capability:         Not included         Layer braided corrosion resistant steel wire err-100      <	
Thread Class:         2b 1st end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.875 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         1.390 inches         Minimum Inside Bending Radius:         9.700 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         End Fitting Component And Material:         Compete fitting stainless steel all ends         Connection Type:         Thread Qty Per Inch (tpi):         12 1st end         Second End Relationship With First End:         Identical         Burst Test Pressure:         12000.0 pounds per square inch         First End Swivel Action Capability:         Not included         Layer Composition And Location:         6th layer braided corrosion resistant steel wire err-100         Maximum Operating Pressure:         0400.0 pounds per square inch         First End Swivel Action Capability:         Not included         Layer Composition And Location:	ross Sectional Shape:
2b ist end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.875 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         1.390 inches         Minimum Inside Bending Radius:         9.700 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Sträght 1st end         End Fitting Component And Material:         Complete fitting stainless steel all ends         Connection Type:         Thread Qty Per Inch (tpi):         12 1st end         Second End Relationship With First End:         Identical         Burst Test Pressure:         12000.0 pounds per square inch         First End Swivel Action Capability:         Not included         Layer Composition And Location:         Bital per square inch         First End Swivel Action Capability:         000.0 pounds per square inch         First End Swivel Action Capability:         Not included         Layer Composition And Location:         Bital set stend         Mou.0 pounds per s	ound
Thread Direction:         Right-hand 1st end         Inside Diameter:         0.875 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         1.390 inches         Minimum Inside Bending Radius:         9.700 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         End Fitting Component And Material:         Complete fitting stainless steel all ends         Connection Type:         Thread Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         12000.0 pounds per square inch         First End Swivel Action Capability:         Not included         Layer Composition And Location:         6th layer braided corrosion resistant steel wire err-100         Maximum Operating Pressure:         4000.0 pounds per square inch         Thread Size:         1.312 inches 1st end	hread Class:
Right-hand 1st end         Inside Diameter:         0.875 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         1.390 inches         Minimum Inside Bending Radius:         9.700 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         End Fitting Component And Material:         Compete fitting stainless steel all ends         Connection Type:         Threaded internal tube 1st end         Thready Qty Per Inch (tpi):         12 1st end         Second End Relationship With First End:         Identical         Burst Test Pressure:         12000.0 pounds per square inch         First End Swivel Action Capability:         Not included         Layer Composition And Location:         Ght ayer braided corrosion resistant steel wire err-100         Maximum Operating Pressure:         000.0 pounds per square inch         Thread Size:         1.312 inches 1st end         Straidel         Straidel Corrosion resistant steel wire err-100         Maximum Operating Pressure: </td <td>b 1st end</td>	b 1st end
Inside Diameter: 0.875 inches  Iempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 1.390 inches  Minimum Inside Bending Radius: 9.700 inches  Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end End Fitting Component And Material: Complete fitting stainless steel all ends Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Second End Relationship With First End: Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Sect Angle: 37.0 degrees 1st end	hread Direction:
0.875 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 1.390 inches Minimun Inside Bending Radius: 9.700 inches Connection Style: Svivel nut flare 1st end End Connection Design: Straight 1st end End Connection Design: Straight 1st end End Fitting Component And Material: Complete fitting stainless steel all ends Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Second End Relationship With First End: Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Sect Angle: 37.0 degrees 1st end	ight-hand 1st end
Tempurature Rating:         -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         1.390 inches         Minimum Inside Bending Radius:         9.700 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         End Fiting Component And Material:         Complete fitting stainless steel all ends         Connection Type:         Threaded internal tube 1st end         Thready Qty Per Inch (tpi):         12 1st end         Second End Relationship With First End:         Identical         Burst Test Pressure:         12000.0 pounds per square inch         First End Swivel Action Capability:         Not included         Layer Composition And Location:         6th layer braided corrosion resistant steel wire err-100         Maximum Operating Pressure:         000.0 pounds per square inch         Thread Size:         1.312 inches 1st end         Second End Relationship Kith Einst End:         Identical         Burst Test Pressure:         12000.0 pounds per square inch         First End Swivel Actoin Capability:	iside Diameter:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single responseOutside Diameter:1.390 inchesMinimum Inside Bending Radius:9.700 inchesConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endEnd Fitting Component And Material:Connection Type:Threaded internal tube 1st endThreaded internal tube 1st endThready Qty Per Inch (tpi):12 1st endSecond End Relationship With First End:IdenticalBurst Test Pressure:12000.0 pounds per square inchFirst End Swivel Action Capability:Not includedLayer Composition And Location:6th layer braided corrosion resistant steel wire err-100Maximum Operating Pressure:1.312 inches 1st endStraiger 1st endStraiger 1st endStraiger 1st endStraiger 2000.0 pounds per square inchFirst End Swivel Action Capability:Not includedLayer Composition And Location:6th layer braided corrosion resistant steel wire err-100Maximum Operating Pressure:1.312 inches 1st endSteel 312 inches 1st endSteel 313 inches 1st endSteel 314 endSteel 315 end37.0 degrees 1st end	.875 inches
Outside Diameter:         1.390 inches         Minimum Inside Bending Radius:         9.700 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         End Fitting Component And Material:         Connection Type:         Threaded internal tube 1st end         Threaded internal tube 1st end         Thready Qty Per Inch (tpi):         12 1st end         Second End Relationship With First End:         Identical         Burst Test Pressure:         12000.0 pounds per square inch         First End Swivel Action Capability:         Not included         Layer Composition And Location:         6th layer braided corrosion resistant steel wire err-100         Maximum Operating Pressure:         1.312 inches 1st end         Streaded Second End Relation Sign Second End Relation Streade Second End Relation Second End Relat	empurature Rating:
<ul> <li>1.390 inches</li> <li>Minimum Inside Bending Radius:</li> <li>9.700 inches</li> <li>Connection Style:</li> <li>Swivel nut flare 1st end</li> <li>End Connection Design:</li> <li>Straight 1st end</li> <li>End Fitting Component And Material:</li> <li>Complete fitting stainless steel all ends</li> <li>Connection Type:</li> <li>Threaded internal tube 1st end</li> <li>Threaded internal tube 1st end</li> <li>Second End Relationship With First End:</li> <li>Identical</li> <li>Burst Test Pressure:</li> <li>12000.0 pounds per square inch</li> <li>First End Swivel Action Capability:</li> <li>Not included</li> <li>Layer Composition And Location:</li> <li>6th layer braided corrosion resistant steel wire err-100</li> <li>Maximum Operating Pressure:</li> <li>1.312 inches 1st end</li> <li>Seat Angle:</li> <li>37.0 degrees 1st end</li> </ul>	5.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Minimum Inside Bending Radius:   9.700 inches   Connection Style:   Swivel nut flare 1st end   End Connection Design:   Straight 1st end   End Fitting Component And Material:   Complete fitting stainless steel all ends   Connection Type:   Threaded internal tube 1st end   Threaded internal tube 1st end   Straight 1st end   Second End Relationship With First End:   Identical   Burst Test Pressure:   12000.0 pounds per square inch   First End Swivel Action Capability:   Not included   Layer Composition And Location:   6th layer braided corrosion resistant steel wire err-100   Maximum Operating Pressure:   4000.0 pounds per square inch   Thread Size:   1.312 inches 1st end   Sect Angle:   37.0 degrees 1st end	utside Diameter:
9.700 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end End Fitting Component And Material: Complete fitting stainless steel all ends Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Second End Relationship With First End: Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Sect Angle: 37.0 degrees 1st end	.390 inches
Connection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endEnd Fitting Component And Material:Complete fitting stainless steel all endsConnection Type:Threaded internal tube 1st endThready Qty Per Inch (tpi):12 1st endSecond End Relationship With First End:IdenticalBurst Test Pressure:12000.0 pounds per square inchFirst End Swivel Action Capability:Not includedLayer Composition And Location:6th layer braided corrosion resistant steel wire err-100Maximum Operating Pressure:4000.0 pounds per square inchThread Size:1.312 inches 1st endSect Angle:37.0 degrees 1st end	inimum Inside Bending Radius:
Swivel nut flare 1st end End Connection Design: Straight 1st end End Fitting Component And Material: Complete fitting stainless steel all ends Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Second End Relationship With First End: Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	.700 inches
End Connection Design: Straight 1st end End Fitting Component And Material: Complete fitting stainless steel all ends Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Second End Relationship With First End: Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	onnection Style:
Straight 1st end         End Fitting Component And Material:         Complete fitting stainless steel all ends         Connection Type:         Threaded internal tube 1st end         Thready Qty Per Inch (tpi):         12 1st end         Second End Relationship With First End:         Identical         Burst Test Pressure:         12000.0 pounds per square inch         First End Swivel Action Capability:         Not included         Layer Composition And Location:         6th layer braided corrosion resistant steel wire err-100         Maximum Operating Pressure:         4000.0 pounds per square inch         Thread Size:         1.312 inches 1st end         Seat Angle:         37.0 degrees 1st end	wivel nut flare 1st end
End Fitting Component And Material: Complete fitting stainless steel all ends Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Second End Relationship With First End: Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	nd Connection Design:
Complete fitting stainless steel all ends Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Second End Relationship With First End: Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	traight 1st end
Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Second End Relationship With First End: Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	nd Fitting Component And Material:
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Second End Relationship With First End: Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	omplete fitting stainless steel all ends
Thready Qty Per Inch (tpi): 12 1st end Second End Relationship With First End: Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	onnection Type:
12 1st end Second End Relationship With First End: Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	hreaded internal tube 1st end
Second End Relationship With First End: Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	hready Qty Per Inch (tpi):
Identical Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	2 1st end
Burst Test Pressure: 12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	econd End Relationship With First End:
12000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	lentical
First End Swivel Action Capability: Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	urst Test Pressure:
Not included Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	2000.0 pounds per square inch
Layer Composition And Location: 6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	irst End Swivel Action Capability:
6th layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	ot included
Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	ayer Composition And Location:
4000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	th layer braided corrosion resistant steel wire err-100
Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	aximum Operating Pressure:
1.312 inches 1st end Seat Angle: 37.0 degrees 1st end	000.0 pounds per square inch
Seat Angle: 37.0 degrees 1st end	hread Size:
37.0 degrees 1st end	.312 inches 1st end
-	eat Angle:
Inside Surface Condition:	7.0 degrees 1st end
	iside Surface Condition:
Smooth	mooth
Measuring Method And Length:	easuring Method And Length:
17.375 inches	7.375 inches

Nonmetallic Hose Assembly - Page 2 of 2



**Special Features:** 

Inner conveying tube material-plastic, polytetrafluoroethylene

**Thread Series Designator:** 

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0