NSN 4720-01-371-7208

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-371-7208

Cross Sectional Shape:			
Round			
Thread Class:			
3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
1.250 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response			
Outside Diameter:			
2.000 inches			
Minimum Inside Bending Radius:			
16.500 inches			
End Application:			
Hyd, power unit, jered brown inc.			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
6500.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided wire and 2nd layer braided wire and outer layer wrapped rubber, synthetic			
Maximum Operating Pressure:			
1625.0 pounds per square inch			
Thread Size:			
1.625 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Hydrostatic Test Pressure:			
2250.0 pounds per square inch			
Outer Covering Environmental Protection:			
Abrasion resistant			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
32.000 inches working			
Media For Which Designed:			
Fuel/oil, hydrocarbon single response			

NSN 4720-01-371-7208

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:	Thread	Series	Designator:
---------------------------	--------	---------------	--------------------

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0