Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-371-9449

| view Online at https://aerobasegroup.com/hsn/4720-01-371-9449 |
|---|
| Cross Sectional Shape: |
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.810 inches |
| Minimum Inside Bending Radius: |
| 4.000 inches |
| End Application: |
| 2320-01-354-3387 |
| Connection Style: |
| Swivel nut, gasket seal 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Perforated outer cover |
| Thready Qty Per Inch (tpi): |
| 16 1st end |
| Burst Test Pressure: |
| 14000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided polyamide cord and outer layer molded polyurethane |
| Maximum Operating Pressure: |
| 3500.0 pounds per square inch |
| Thread Size: |
| 0.812 inches 1st end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 79.000 inches |
| Thread Series Designator: |
| Un 1st end |
| Shelf Life: |
| N/a |

NSN 4720-01-371-9449

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0