

View Online at <https://aerobasegroup.com/nsn/4720-01-372-1514>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

**Outside Diameter:**

0.490 inches

**Minimum Inside Bending Radius:**

3.000 inches

**Connection Style:**

Flared 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Connection Type:**

Unthreaded external hose 2nd end

**Features Provided:**

Reusable end fittings

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

1000.0 pounds per square inch

**First End Swivel Action Capability:**

Included

**Layer Composition And Location:**

1st layer braided textile yarn err-100

**Maximum Operating Pressure:**

250.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant

**Vacuum In Torr:**

28.0

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

24.000 inches

**Inside Diameter Hose Accommodated:**

0.250 inches 2nd end

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0