NSN 4720-01-372-7303Nonmetallic Hose Assembly - Page 1 of 2



Noninetallic Hose Assembly - Page 1 of 2	Group
View Online at https://aerobasegroup.com/nsn/4720-01-372-7303	
Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.430 inches	
Minimum Inside Bending Radius:	
0.750 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Perforated outer cover	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided fiber and outer layer molded polyurethane	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.125 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Outer Covering Environmental Protection:	
Abrasian registant	

Abrasion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

22.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon and water single response

Thread Series Designator:

Jic 1st end

NSN 4720-01-372-7303

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0