

View Online at <https://aerobasegroup.com/nsn/4720-01-372-9705>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.375 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

1.750 inches

Minimum Inside Bending Radius:

11.000 inches

End Application:

Hc130n, weatherhead company

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer rubber impregnated braided steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

1.8750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and hydraulic solution resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.000 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0