NSN 4720-01-373-0485

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-373-0485

Cross Sectional Shape:			
Round			
Thread Class:			
2b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.750 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response			
Outside Diameter:			
1.030 inches			
Minimum Inside Bending Radius:			
12.000 inches			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 2nd end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Reusable end fittings			
Thready Qty Per Inch (tpi):			
12 1st end			
Burst Test Pressure:			
1000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided fiber and outer layer molded rubber, synthetic			
Maximum Operating Pressure:			
250.0 pounds per square inch			
Thread Size:			
1.062 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Hydrostatic Test Pressure:			
500.0 pounds per square inch			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
24.000 inches			
Media For Which Designed:			

Fuel/oil, hydrocarbon single response

NSN 4720-01-373-0485

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:
--------	--------	--------------------

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0