NSN 4720-01-373-2713

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-373-2713

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
2.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
2.500 inches
Minimum Inside Bending Radius:
12.000 inches
Exterior Color:
Blue
Hose Or Tubing Specification/std Data:
Sa3 j517, 100r4-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting zinc 1st end
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
400.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided textile yarn err-100
Maximum Operating Pressure:
100.0 pounds per square inch
Thread Size:
2.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:

Smooth

NSN 4720-01-373-2713

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
19.250 inches
Second End Swivel Action Capability:
Not included
Special Features:
Inner conveying tube material-rubber, polyethylene
Thread Series Designator:
Npt 2nd end
Specification Data:
Sa3 j517, 100r4-81343 national std/spec
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A542a0