

View Online at <https://aerobasegroup.com/nsn/4720-01-373-3112>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.312 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.375 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Black or gray

Quick Disconnect Size:

0.750 inches 2nd end

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

1st layer cotton and 2nd layer rubber impregnated braided steel wire and outer layer rubber impregnated cotton fabric

Maximum Operating Pressure:

2000.0 pounds per square inch

Thread Size:

0.5625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

4500.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

84.000 inches working

Special Features:

Sleeving, elec.Blk..750 id, per mil-i-23053-5; body, quick disconnect, 6558519-2

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Reference Number Differentiating Characteristics:

As differentiated by material

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0