## NSN 4720-01-373-5635

Nonmetallic Hose Assembly - Page 1 of 2

**AeroBase** Group

View Online at https://aerobasegroup.com/nsn/4720-01-373-5635

Cross Sectional Shape: Round Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.500 inches Minimum Inside Bending Radius: 2.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic Maximum Operating Pressure: 250.0 pounds per square inch Thread Size:
Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.500 inches Minimum Inside Bending Radius: 2.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic Maximum Operating Pressure: 250.0 pounds per square inch
Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.500 inches Minimum Inside Bending Radius: 2.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic Maximum Operating Pressure: 250.0 pounds per square inch
Inside Diameter:  0.250 inches  Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response  Outside Diameter: 0.500 inches  Minimum Inside Bending Radius: 2.500 inches  Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end  Connection Type: Threaded internal tube 1st end  Burst Test Pressure: 1000.0 pounds per square inch  Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure: 250.0 pounds per square inch
Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response  Outside Diameter: 0.500 inches  Minimum Inside Bending Radius: 2.500 inches  Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end  Connection Type: Threaded internal tube 1st end  Burst Test Pressure: 1000.0 pounds per square inch  Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure: 250.0 pounds per square inch
Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response  Outside Diameter: 0.500 inches  Minimum Inside Bending Radius: 2.500 inches  Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end  Connection Type: Threaded internal tube 1st end  Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure: 250.0 pounds per square inch
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response  Outside Diameter:  0.500 inches  Minimum Inside Bending Radius:  2.500 inches  Connection Style:  Swivel nut flare 1st end  End Connection Design:  Straight 1st end  Connection Type:  Threaded internal tube 1st end  Burst Test Pressure:  1000.0 pounds per square inch  Layer Composition And Location:  1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure:  250.0 pounds per square inch
Outside Diameter:  0.500 inches  Minimum Inside Bending Radius:  2.500 inches  Connection Style:  Swivel nut flare 1st end  End Connection Design:  Straight 1st end  Connection Type:  Threaded internal tube 1st end  Burst Test Pressure:  1000.0 pounds per square inch  Layer Composition And Location:  1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure:  250.0 pounds per square inch
Minimum Inside Bending Radius:  2.500 inches  Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end  Connection Type: Threaded internal tube 1st end  Burst Test Pressure:  1000.0 pounds per square inch  Layer Composition And Location:  1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure:  250.0 pounds per square inch
Minimum Inside Bending Radius:  2.500 inches  Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end  Connection Type: Threaded internal tube 1st end  Burst Test Pressure: 1000.0 pounds per square inch  Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure: 250.0 pounds per square inch
2.500 inches  Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic Maximum Operating Pressure: 250.0 pounds per square inch
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic Maximum Operating Pressure: 250.0 pounds per square inch
Swivel nut flare 1st end  End Connection Design: Straight 1st end  Connection Type: Threaded internal tube 1st end  Burst Test Pressure: 1000.0 pounds per square inch  Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure: 250.0 pounds per square inch
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic Maximum Operating Pressure: 250.0 pounds per square inch
Straight 1st end  Connection Type: Threaded internal tube 1st end  Burst Test Pressure: 1000.0 pounds per square inch  Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure: 250.0 pounds per square inch
Connection Type: Threaded internal tube 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic Maximum Operating Pressure: 250.0 pounds per square inch
Threaded internal tube 1st end  Burst Test Pressure:  1000.0 pounds per square inch  Layer Composition And Location:  1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure:  250.0 pounds per square inch
Burst Test Pressure:  1000.0 pounds per square inch  Layer Composition And Location:  1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure:  250.0 pounds per square inch
1000.0 pounds per square inch  Layer Composition And Location:  1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure:  250.0 pounds per square inch
Layer Composition And Location:  1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure:  250.0 pounds per square inch
1st layer braided textile yarn and outer layer molded rubber, synthetic  Maximum Operating Pressure:  250.0 pounds per square inch
Maximum Operating Pressure: 250.0 pounds per square inch
250.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.500 inches
Special Features:
As require electrical sleeving per mil-i-23053-5, part no. M23053-5-109-9 with special markings
Media For Which Designed:
Fuel/oil, hydrocarbon and water and hydraulic fluid, water base and air single response
Thread Series Designator:
Jic 1st end
Reference Number Differentiating Characteristics:
As differentiated by special features
Shelf Life:
N/a

## NSN 4720-01-373-5635

Nonmetallic Hose Assembly - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A542a0