NSN 4720-01-373-5646



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-373-5646 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 0.630 inches **Minimum Inside Bending Radius:** 3.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 500.0 pounds per square inch **Vacuum In Torr:**

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

78.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-373-5646

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	-00.9.	

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0