NSN 4720-01-373-7785

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-373-7785

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.313 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.672 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black or gray
Connection Style: Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
1st layer cotton and 2nd layer rubber impregnated braided steel wire and outer layer wrapped rubber, synthetic
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.5625 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
84.000 inches
Special Features:
Sleeving, elec.Black, 0.750 id.Per m23053-5-109-0
Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-373-7785

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Des	ignator:
-------------------	----------

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0