NSN 4720-01-373-7788

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-373-7788

view Offiline at https://aerobasegroup.com/hish/+//20-01-5//3-1//00
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.620 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.860 inches
Minimum Inside Bending Radius:
3.880 inches
Connection Style:
Swivel nut with compression sleeve 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and grease resistant and heat resistant and hydraulic solution resistant and oil resistant and solvent resistant and vibration
resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:

15.000 inches

NSN 4720-01-373-7788

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator
Unj 1st end

, ...

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0