## NSN 4720-01-373-9877

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-373-9877 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.630 inches **Minimum Inside Bending Radius:** 3.000 inches **Exterior Color:** Black **End Connection Design:** Straight 1st end **End Fitting Component And Material:** Complete fitting copper alloy all ends **Connection Type:** Threaded internal tube 1st end **Second End Relationship With First End:** Identical **Burst Test Pressure:** 500.0 pounds per square inch First End Swivel Action Capability: Included **Layer Composition And Location:** 1st layer braided textile yarn err-100 **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Vacuum In Torr:** 28.0 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 

20.000 inches

# NSN 4720-01-373-9877

Nonmetallic Hose Assembly - Page 2 of 2



#### **Special Features:**

Socket, quick-connect, part no.Bvhn-4-4fn.Fscm 78357; sleeving, elec.0.750 id.Black

#### Media For Which Designed:

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf 1st end

### **Reference Number Differentiating Characteristics:**

As differentiated by material

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0