Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-374-1212

Cross Sectional Sh	lape:
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.410 inches	
Tempurature Ratin	g:
-40.0 degrees fahre	nheit and 212.0 degrees fahrenheit single response
Outside Diameter:	
0.770 inches	
Minimum Inside Be	ending Radius:
4.620 inches	
Connection Style:	
Swivel nut flare 1st	and
End Connection De	esign:
Straight 1st end	
Connection Type:	
Threaded internal tu	be 1st end
Layer Composition	And Location:
1st layer braided tex	tile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operatin	g Pressure:
625.0 pounds per so	juare inch
Thread Size:	
0.750 inches 1st end	t
Seat Angle:	
37.0 degrees 1st en	d
Inside Surface Con	dition:
Smooth	
Measuring Method	And Length:
23.750 inches	
Media For Which D	esigned:
Fuel/oil, hydrocarbo	on single response
Thread Series Desi	gnator:
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	

NSN 4720-01-374-1212

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

