## NSN 4720-01-374-1214

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-374-1214

Craca Scational Shape.
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.120 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
9.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1800.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
450.0 pounds per square inch
Thread Size:
1.625 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
900.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
38.750 inches
Special Features:
Includes strap and tag
Media For Which Designed:
Fuel/oil, hydrocarbon and water single response
Thread Series Designator:

Jic 1st end

## NSN 4720-01-374-1214

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0