NSN 4720-01-374-1216

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-374-1216 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.120 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 1.500 inches **Minimum Inside Bending Radius:** 9.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 1800.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 450.0 pounds per square inch **Thread Size:** 1.625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

900.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

9.250 inches

Media For Which Designed:

Fuel/oil, hydrocarbon and water single response

Thread Series Designator:

Jic 1st end

Shelf Life:

N/a

NSN 4720-01-374-1216

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0