## NSN 4720-01-374-2473

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-374-2473

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-35.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.880 inches
Angle Between Rigid Elbow Fittings In Deg:
13.0
End Application:
Sub ceg, raytheon co.
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 2nd end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
800.0 pounds per square inch
First End Swivel Action Capability:
Included
Layer Composition And Location:
Outer layer polyester err-100
Maximum Operating Pressure:
235.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end

## NSN 4720-01-374-2473

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
25.000 inches
Special Features:
Swage hose coupling two places
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0