

View Online at <https://aerobasegroup.com/nsn/4720-01-374-3894>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.560 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Clear

Connection Style:

Plain 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external tube 1st end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

0.250 inches 1st end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Outer Covering Environmental Protection:

Weatherproof and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

36.000 inches

Special Features:

With two-way-shutoff first end part number II2-h16, fscm hanson co.

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0