

View Online at <https://aerobasegroup.com/nsn/4720-01-375-1390>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Flange Thickness:

0.315 inches 2nd end

Outside Diameter:

2.000 inches

Minimum Inside Bending Radius:

16.500 inches

Center To Center Distance Between Bolt Holes Along Width:

1.120 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.312 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.090 inches and 3.160 inches 2nd end

End Application:

2350-01-305-0028, howitzer, medium, self-propelled

Flange Width:

3.160 inches 2nd end

Connection Style:

Plain 2nd end

Bolt Hole Diameter:

0.469 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external pipe 1st end

Burst Test Pressure:

10000.0 pounds per square inch

Layer Composition And Location:

1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, ethylene propylene

Maximum Operating Pressure:

2500.0 pounds per square inch

Thread Size:

1.000 inches 1st end

Hydrostatic Test Pressure:

5000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.500 inches

Flange Style:

Double oval (sae split type flange) 2nd end

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0