

View Online at <https://aerobasegroup.com/nsn/4720-01-375-6307>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

0.590 inches

Minimum Inside Bending Radius:

7.000 inches

Hose Or Tubing Specification/std Data:

Sae j517, 100r2, type at-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel, plain 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded external tube 1st end

Features Provided:

Nonskive

Second End Relationship With First End:

Not identical

Burst Test Pressure:

14000.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

Outer layer wrapped rubber, synthetic err-100

Maximum Operating Pressure:

3500.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Weatherproof and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

120.000 inches

Second End Swivel Action Capability:

Included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Specification Data:

Sae j517, 100r2, type at-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0