NSN 4720-01-376-2702

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-376-2702 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.940 inches **Minimum Inside Bending Radius:** 2.250 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and 2nd layer braided wire and outer layer braided textile yarn **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 2500.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 20.750 inches **Special Features:** Includes a 4.000 in. Id tiedown strip per mil-s-23190 **Thread Series Designator:** Unf 1st end Shelf Life:

N/a

NSN 4720-01-376-2702

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0