## NSN 4720-01-376-2703



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-376-2703 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.940 inches **Minimum Inside Bending Radius:** 2.250 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and 2nd layer braided wire and outer layer braided textile yarn **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 2500.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 19.500 inches **Special Features:** Includes a 4.000 in. Id tiedown strap per mil-s-23190

**Thread Series Designator:** Unf 1st end

Shelf Life:

N/a

## NSN 4720-01-376-2703

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0