## NSN 4720-01-376-4263

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-376-4263

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.212 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response				
Outside Diameter:				
0.485 inches				
Minimum Inside Bending Radius:				
3.000 inches				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
24 1st end				
Burst Test Pressure:				
16000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided cotton cord and outer layer braided wire				
Maximum Operating Pressure:				
4000.0 pounds per square inch				
Thread Size:				
0.562 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
8000.0 pounds per square inch				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
99.000 inches				
Media For Which Designed:				
Fuel/oil, hydrocarbon single response				
Thread Series Designator:				

Unj 1st end

## NSN 4720-01-376-4263

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0