## NSN 4720-01-376-5639



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-376-5639 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.298 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response **Outside Diameter:** 0.688 inches **Minimum Inside Bending Radius:** 2.500 inches **End Application:** C-17a aircraft **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Elbow 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 16000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fiber and outer layer molded polytetrafluoroethylene **Maximum Operating Pressure:** 4000.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 8000.0 pounds per square inch

Flow Angle: 45.0 degrees 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 17.250 inches

## NSN 4720-01-376-5639

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0