

View Online at <https://aerobasegroup.com/nsn/4720-01-377-3028>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Outside Diameter:

Between 1.594 inches and 1.719 inches

Minimum Inside Bending Radius:

4.500 inches

Angle Between Rigid Elbow Fittings In Deg:

305.0

End Application:

1520-01-125-5476

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Elbow 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability and self-sealing

Thready Qty Per Inch (tpi):

16 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

400.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer helix copper coil err-100

Maximum Operating Pressure:

100.0 pounds per square inch

Thread Size:

1.188 inches 1st end

Hydrostatic Test Pressure:

200.0 pounds per square inch

Flow Angle:

45.0 degrees 1st end

Outer Covering Environmental Protection:

Abrasion resistant and mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.000 inches working

Special Features:

Inner conveying tube material-rubber, buna-n

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0