NSN 4720-01-377-3120

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-377-3120

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.298 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.655 inches
Minimum Inside Bending Radius:
2.500 inches
End Application:
Mcdonnell douglas c-17a aircraft
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided polyamide cord
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
10.875 inches
Thread Series Designator:
Unjf 1st end

NSN 4720-01-377-3120

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0