

View Online at <https://aerobasegroup.com/nsn/4720-01-377-3150>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.437 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

0.812 inches

Minimum Inside Bending Radius:

8.000 inches

Connection Style:

Plain 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

24000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer spirally wrapped steel fabric and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

6000.0 pounds per square inch

Thread Size:

1.750 inches 1st end

Hydrostatic Test Pressure:

12000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

32.000 inches

Special Features:

C.P.V.Male o-ring;

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0