NSN 4720-01-377-4004

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-377-4004

Ones On the sel Ohama					
Cross Sectional Shape:					
Round Thread Class					
Thread Class:					
2b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.406 inches					
Tempurature Rating:					
-22.0 degrees fahrenheit and 250.0 degrees fahrenheit single response					
Outside Diameter:					
0.770 inches					
Minimum Inside Bending Radius:					
3.125 inches					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Features Provided:					
Reusable end fittings					
Burst Test Pressure:					
1750.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided textile yarn and outer layer molded rubber, synthetic					
Maximum Operating Pressure:					
350.0 pounds per square inch					
Thread Size:					
0.750 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
700.0 pounds per square inch					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
17.000 inches					
Media For Which Designed:					
Refrigerant 12 and refrigerant 13 single response					
Thread Series Designator:					
miraa oeneo beolynator.					

Unf 1st end

NSN 4720-01-377-4004

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0