

View Online at <https://aerobasegroup.com/nsn/4720-01-377-6632>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

0.780 inches

Minimum Inside Bending Radius:

5.000 inches

End Application:

Abg t/s, parker hannifin corp.

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and outer layer wrapped rubber, synthetic

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

7.400 inches

Special Features:

Sleeving, elec.White, 1.500 id.Per m23053-5-111-9

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0