NSN 4720-01-377-6632

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-377-6632

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.780 inches
Minimum Inside Bending Radius:
5.000 inches
End Application:
Abg t/s, parker hannifin corp.
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer wrapped rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
7.400 inches
Special Features:
Sleeving, elec.White, 1.500 id.Per m23053-5-111-9

Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-377-6632

Nonmetallic Hose Assembly - Page 2 of 2



Thread S	Series	Designator:
----------	--------	-------------

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0