NSN 4720-01-377-6879



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-377-6879 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.380 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.690 inches **Minimum Inside Bending Radius:** 5.000 inches **End Application:** 3930-01-158-0849 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and outer layer wrapped rubber, synthetic **Maximum Operating Pressure:** 2250.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 35.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:**

Thread Series Design Unf 1st end Shelf Life:

N/a

NSN 4720-01-377-6879

Nonmetallic Hose Assembly - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV | еа | SU | ıre: |

--

Demilitarization:

No

Fiig:

A542a0