Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-377-7524

New Online at https://aerobasegroup.com/nsi//4720-01-577-7524
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.530 inches
Minimum Inside Bending Radius:
4.000 inches
End Application:
3930-01-158-0849
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1100.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and outer layer wrapped rubber, synthetic
Maximum Operating Pressure:
2750.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
28.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end

NSN 4720-01-377-7524

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0