## NSN 4720-01-378-4184

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-378-4184

Thread Class
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.625 inches
Minimum Inside Bending Radius:
3.250 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.875 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
72.000 inches working
Thread Series Designator:
Unf 2nd end

## NSN 4720-01-378-4184

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0