Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-378-7593

С	ross Sectional Shape:
R	ound
Т	hread Class:
2	b 1st end
Т	hread Direction:
R	ight-hand 1st end
In	nside Diameter:
0.	500 inches
T	empurature Rating:
-4	10.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
0	utside Diameter:
0.	780 inches
Μ	linimum Inside Bending Radius:
5.	.000 inches
С	onnection Style:
S	wivel nut flare 1st end
Ε	nd Connection Design:
S	traight 1st end
С	onnection Type:
Т	hreaded internal tube 1st end
В	urst Test Pressure:
10	000.0 pounds per square inch
L	ayer Composition And Location:
1:	st layer braided textile yarn and outer layer molded rubber, synthetic
Μ	laximum Operating Pressure:
2	50.0 pounds per square inch
Т	hread Size:
0.	.688 inches 1st end
S	eat Angle:
3	7.0 degrees 1st end
Н	ydrostatic Test Pressure:
5	00.0 pounds per square inch
V	acuum In Torr:
5	0.8
	side Surface Condition:
S	mooth
	leasuring Method And Length:
	6.000 inches
	ledia For Which Designed:
	uel/oil, hydrocarbon single response
	hread Series Designator:
U	nf 1st end

NSN 4720-01-378-7593

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0