Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-378-8055

ss Sectional Shape:	
ind	
ead Class:	
lst end	
ead Direction:	
nt-hand 1st end de Diameter:	
00 inches	
purature Rating:	
0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response	se
side Diameter:	
30 inches	
imum Inside Bending Radius:	
00 inches	
I Connection Design:	
ight 1st end	
I Fitting Component And Material:	
nplete fitting copper alloy all ends	
inection Type:	
eaded internal tube 1st end	
ond End Relationship With First End:	
ntical	
st Test Pressure:	
0.0 pounds per square inch	
t End Swivel Action Capability:	
included	
er Composition And Location:	
er layer molded rubber, synthetic err-100	
kimum Operating Pressure:	
.0 pounds per square inch	
ead Size:	
50 inches 1st end	
t Angle:	
) degrees 1st end	
Irostatic Test Pressure:	
.0 pounds per square inch	
uum In Torr:	
3	
de Surface Condition:	
poth	
asuring Method And Length:	
000 inches	

NSN 4720-01-378-8055 Nonmetallic Hose Assembly - Page 2 of 2



Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0