

View Online at <https://aerobasegroup.com/nsn/4720-01-378-8722>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.298 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.469 inches

Minimum Inside Bending Radius:

4.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

96.000 inches excluding end fittings

Special Features:

Attachments on one end includes: 1 union, p/n an815-8d; 1 tee, p/n an938d8; 1 valve, p/n ms28882-8; 5 o-ring, p/n ms29512-08; 1 socket, p/n st7m322-8; 1 nipple, p/n st7m324-8; 1 cap, p/n st7m377-8; 1 plug, p/n st7m378-8; 1 filter, p/n st7m385-1; 3 sleeve, p/n 9m306-6; 1 cable, p/n 9m59-2-230p; u/o f15e aircraft

Thread Series Designator:

Unf 1st end

Reference Number Differentiating Characteristics:

As differentiated by special features

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0