NSN 4720-01-379-5458

Cross Sectional Shape:

Assy has lip seal end fittings

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-379-5458

Round			
Thread Class:			
2b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.391 inches			
Tempurature Rating:			
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response			
Outside Diameter:			
0.708 inches			
Minimum Inside Bending Radius:			
3.250 inches			
Connection Style:			
Swivel nut flare 2nd end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Thready Qty Per Inch (tpi):			
18 1st end			
Burst Test Pressure:			
12000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
3000.0 pounds per square inch			
Thread Size:			
0.844 inches 2nd end			
Seat Angle:			
37.0 degrees 2nd end			
Hydrostatic Test Pressure:			
6000.0 pounds per square inch			
Flow Angle:			
90.0 degrees 2nd end			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
70.000 inches working			
Special Features:			

NSN 4720-01-379-5458

Nonmetallic Hose Assembly - Page 2 of 2



	•		
Thread	Series	I)esian	ator:

Unjs 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0