## NSN 4720-01-379-7201

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-379-7201

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.313 inches
Tempurature Rating:
-77.0 degrees fahrenheit single response and 650.0 degrees fahrenheit single response
Outside Diameter:
0.510 inches
Minimum Inside Bending Radius:
1.560 inches
Inner Conveying Tube Style:
Annular open-pitch corrugated
End Application:
Mcdonnell douglas c-17a aircraft
Connection Style:
Swivel nut with loose or integral clinch sleeve 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1540.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
385.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
770.0 pounds per square inch

**Thread Series Designator:** 

**Measuring Method And Length:** 

9.500 inches working

45.0 degrees 2nd end

Unjf 1st end

Flow Angle:

## NSN 4720-01-379-7201

Metallic Hose Assembly - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0