Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-381-3869

Croce Sectional Shana	
Cross Sectional Shape: Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response	
Outside Diameter:	
0.750 inches	
Minimum Inside Bending Radius:	
4.000 inches	
End Application:	
4940-00-249-7315	
Connection Style:	
Inverted flare 2nd end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
4500.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber	, synthetic
Maximum Operating Pressure:	
1125.0 pounds per square inch	
Thread Size:	
0.375 inches 2nd end	
Seat Angle:	
30.0 degrees 2nd end	
Hydrostatic Test Pressure:	
2250.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
30.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Npt 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0