Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-382-1647

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.690 inches
Minimum Inside Bending Radius:
2.500 inches
Exterior Color:
Black
End Application:
2320-01-354-4528
Connection Style:
Gasket seal / optional end 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal boss 2nd end
Thready Qty Per Inch (tpi):
16 2nd end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer braided synthetic cord
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.688 inches 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 18.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un 2nd end Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fig: A542a0