NSN 4720-01-382-1713



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-382-1713 **Cross Sectional Shape:** Round **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.310 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.620 inches **Minimum Inside Bending Radius:** 5.000 inches **Exterior Color:** Black **End Application:** 2350-01-354-5657 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 500.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant **Vacuum In Torr:**

28.0

Inside Surface Condition:

Smooth

NSN 4720-01-382-1713

Nonmetallic Hose Assembly - Page 2 of 2



Measuring	Method	And	Length:
-----------	--------	-----	---------

59.000 inches excluding end fittings

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

•

Shelf Life:

Unit Of Measure:

--

N/a

Demilitarization:

No

Fiig:

A542a0