Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-382-2058

| Cross Sectional Shape:<br>Round<br>Thread Class:<br>3b 1st end<br>Thread Direction:<br>Right-hand 1st end<br>nside Diameter:<br>0.298 inches<br>Tempurature Rating:<br>65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response<br>Dutside Diameter: |
|--|
| Thread Class:<br>3b 1st end<br>Thread Direction:<br>Right-hand 1st end<br>nside Diameter:<br>0.298 inches<br>Tempurature Rating:<br>65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response   |
| Bb 1st end   Thread Direction:   Right-hand 1st end   nside Diameter:   0.298 inches   Tempurature Rating:   65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response  |
| Thread Direction:<br>Right-hand 1st end<br>nside Diameter:<br>0.298 inches<br>Tempurature Rating:<br>65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response  |
| Right-hand 1st end<br><b>nside Diameter:</b><br>).298 inches<br><b>Fempurature Rating:</b><br>65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response   |
| nside Diameter:<br>).298 inches<br>Fempurature Rating:<br>65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response   |
| 0.298 inches<br><b>Fempurature Rating:</b><br>65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response   |
| <b>Fempurature Rating:</b><br>65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response   |
| 65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response   |
|  |
| Jutside Diameter:  |
|  |
| ).575 inches   |
| Ainimum Inside Bending Radius:   |
| 5.000 inches   |
| Connection Style:  |
| Swivel nut, gasket seal 2nd end  |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Fhready Qty Per Inch (tpi):  |
| 20 2nd end   |
| Burst Test Pressure:   |
| 6000.0 pounds per square inch  |
| ayer Composition And Location:   |
| Duter layer braided corrosion resistant steel wire   |
| Maximum Operating Pressure:  |
| 1000.0 pounds per square inch  |
| Thread Size:   |
| 0.719 inches 2nd end   |
| lydrostatic Test Pressure:   |
| 3000.0 pounds per square inch  |
| Flow Angle:  |
| I5.0 degrees 2nd end   |
| nside Surface Condition:   |
| Smooth   |
| Measuring Method And Length:   |
| 04.000 inches  |
| Fhread Series Designator:  |
| Jnjs 2nd end   |
| Shelf Life:  |
| N/a  |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0