## NSN 4720-01-382-6519

Nonmetallic Hose Assembly - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/4720-01-382-6519

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 1.250 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit single response and 257.0 degrees fahrenheit single response                                   |
| Flange Thickness:   |
| 0.315 inches 2nd end  |
| Outside Diameter:   |
| 1.850 inches  |
| Minimum Inside Bending Radius:  |
| 16.500 inches   |
| Hose Or Tubing Specification/std Data:  |
| Sae j517, 100r12-81343 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Center To Center Distance Between Bolt Holes Along Width:   |
| 1.188 inches 2nd end  |
| Center To Center Distance Between Bolt Holes Along Length:  |
| 2.312 inches 2nd end  |
| Bolt Hole Quantity:   |
| 4 2nd end   |
| Flange Length:  |
| 3.090 inches 2nd end and 3.160 inches 2nd end   |
| End Application:  |
| Allied systems co. Electric/hydraulic crane   |
| Flange Width:   |
| 2.780 inches 2nd end  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| Bolt Hole Diameter:   |
| 0.469 inches 2nd end  |
| End Flange Construction:  |
| Solid 2nd end   |
| End Connection Design:  |
| Straight 1st end  |
| End Fitting Component And Material:   |
| Complete fitting stainless steel all ends   |
| Connection Type:  |

Threaded internal tube 1st end

## NSN 4720-01-382-6519

Features Provided:

Nonmetallic Hose Assembly - Page 2 of 3



| i eatures i rovided.                            |
|---|
| Nonskive  |
| Thready Qty Per Inch (tpi):                     |
| 12 1st end                                      |
| Second End Relationship With First End:         |
| Not identical                                   |
| Burst Test Pressure:                            |
| 12000.0 pounds per square inch                  |
| First End Swivel Action Capability:             |
| Not included                                    |
| Layer Composition And Location:                 |
| 1st layer spirally wrapped steel fabric err-100 |
| Maximum Operating Pressure:                     |
| 3000.0 pounds per square inch                   |
| Thread Size:                                    |
| 1.625 inches 1st end                            |
| Seat Angle:                                     |
| 37.0 degrees 1st end                            |
| Hydrostatic Test Pressure:                      |
| 6000.0 pounds per square inch                   |
| Flow Angle:                                     |
| 90.0 degrees 2nd end                            |
| Inside Surface Condition:                       |
| Smooth  |
| Measuring Method And Length:                    |
| 34.000 inches                                   |
| Second End Swivel Action Capability:            |
| Not included                                    |
| Flange Style:                                   |
| Double oval (sae split type flange) 2nd end     |
| Special Features:                               |
| Inner conveying tube material-rubber, synthetic |
| Media For Which Designed:                       |
| Fuel/oil, hydrocarbon single response           |
| Thread Series Designator:                       |
| Un 1st end                                      |
| Specification Data:                             |
| Sae j517, 100r12-81343 national std/spec        |
| Shelf Life:                                     |
| N/a   |
| Unit Of Measure:                                |
|   |
| Demilitarization:                               |
| No  |

No

## NSN 4720-01-382-6519

Nonmetallic Hose Assembly - Page 3 of 3  $\,$ 



Fiig:

A542a0