Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-382-8870

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
1.000 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single respon	se
Outside Diameter:	
1.500 inches	
Minimum Inside Bending Radius:	
12.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Fhreaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
12 1st end	
Burst Test Pressure:	
6000.0 pounds per square inch	
ayer Composition And Location:	
st layer spirally laid steel wire and 2nd layer spirally laid steel wire a	nd 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire
and outer layer molded rubber, synthetic	
Maximum Operating Pressure:	
000.0 pounds per square inch	
Thread Size:	
1.312 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Outer Covering Environmental Protection:	
Oil resistant and weatherproof	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
88.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon and water and air and hydraulic fluid, water b	ase single response
Thread Series Designator:	
Un 1st end	
Maximum Operating Pressure:4000.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:37.0 degrees 1st endOuter Covering Environmental Protection:Oil resistant and weatherproofInside Surface Condition:SmoothMeasuring Method And Length:88.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon and water and air and hydraulic fluid, water beThread Series Designator:Un 1st end	ase single response

NSN 4720-01-382-8870

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

